

Τελευταία ανανέωση υλικού:

Σύντομη περιγραφή:

T.:

W.:



Business Unit:

TOP-330-PLUS-2 / SPOT VARNISH AND DIE CUTTING



Machine for cost-efficient, high quality converting and finishing. Features winding, cold foiling, super varnishing, Semi or full flexo printing, semi- or full rotary die cutting, IML system, slitting and sheeting. The optimal solution for high productivity. Fully servo driven.

TOP-330-PLUS-2

OPTION WIDTH 420MM/520MM

Max Web Width	330 mm
Max Die-cutting speed (full-rotary)	110m/ min
Max Die-cutting Speed (semi-rotary)	60 m/min
Max Flexo Printing Speed (full-rotary)	90 m / min
Max Flexo Printing Speed (semi-rotary)	60 m / min
Accuracy of Flexo Register	±0.15 mm
Max Unwinder dia.	700 mm
Max Rewinder dia.	700 mm
Min Slitting width	16 mm
Accuracy of Adhesive Cutting	±0.15 mm
Accuracy of IML Cutting	±0.25 mm
Total Motor Power	19 KW ~ 21 KW
Registration	Mark Sensor
Dimension	3650 × 1260 × 2025 mm
Weight	3600 KGS



UNWINDER & WEB GUIDING

Unwinder with closed-loop tension control. Electronic web guide with ultrasonic edge guide sensor. 76 mm air expanding mandrel. Max diameter 700 mm - 1000 mm roll capacity.



SLITTING OPTIONS

Add shear slitting knives. Increase productivity with automatic shear slitting to control the knives from the user-interface. Optional further automation and razorblades.

FLEXO PRINTING UNIT

Independent, servo-driven semi-or full rotary printing unit with auto pre-positioning and registration. Optional reverse side printing. Printing repeat lengths of 50 mm - 457 mm.



COLD FOIL & SUPER VARNISH

Cold-foil and super varnish with two pneumatic shafts and unwind/rewind.



SEMI- OR FULL ROTARY DIE CUTTING

Independent and servo-driven. Repeat lengths from 50 mm - 330 mm for semi-rotary, and 190.5 mm - 476.25 mm for full rotary. Magnetic or solid/engraved cylinders.



IML SYSTEM

IML die-cutting system designed for easy installation and removal. Static eliminator in label output collection table works with counter and stepless speed regulation.



REWINDING OPTIONS

Standard single rewind. Upgrade to dual rewind, or a productive Turret with buffer and automatic cutting of the web for optimal productivity

The optimal solution for high productivity



NOVACEL HELLAS

Θέση Πάτημα, ΒΙ.ΠΕ. Καλυβίων
Καλύβια Θορικού, 190 10 (Τ.Θ. 101)

T.: 210 220 6100, 22990 61000

E.: info@novacel.gr

W.: www.novacel.gr

